



Ancillary, Hospitality, Residential, Retail



Downlights

Architectural








Prism Pro Fire Rated









Category

Application

Specification



PRODUCT FEATURES

- IP65 dimmable LED Fire Rated Downlight suitable for residential and hospitality applications CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- · Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations
- a choice of 2 outputs, in one luminaire
- Remote driver with 2x1.5mm, + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Wide 65° beam angle for increased light distribution

GENERAL INFORMATION	
Wattage	5W - 7W
Lumens Delivered	560lm - 740lm
Lm/W	110lm/W - 105lm/W
Beam Angle	65
CRI	80
CCT	2700/3000/4000/6000K
Input	220-240V
Operating Temp	-20°C - 35°C
SDCM	6
UGR	25
Cut-Out Size	73mm
Product Weight without Packaging	2.85 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
Fire Rated	Yes	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 60,000h	
Warranty (Years)	7	
CE Mark	Yes	
Diameter	90 mm	
Height	62 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750